CLASS 1

Building Product Information Sheet

Product Name:

Powder Coated Galvanised Steel Louvre Vents

Product Descriptions and its intended use:

Powder Coated Galvanised Steel Louvre Vents are designed for use with various claddings. Powder Coated Galvanised Steel Louvre Vents are used to provide ventilation, allowing air in and out while protecting from wind driven rain.

Key technical specifications

* Material : Hot dipped galvanised steel
* Paint : Powder Coated
* Thickness : 0.55 mm
  0.95 mm (P/N 41088)

Product identifier(s):

41080,41082,41086,41088

Place of Manufacture: ☒ Aotearoa New Zealand ☐ Overseas

Legal and trading name of manufacturer(s)

Sigma Sheetmetal Products Ltd

Address for service:

STREET NAME:	24 Princes Street	SUBURB:	Onehunga
CITY, COUNTRY:	Auckland, New Zealand	POSTCODE:	1061

Website:	http://www.sigmasheet.co.nz
Email Address:	Sales@sigmasheet.co.nz
Phone no.:	09 636 3657
NZBN:	9429038071027

Relevant Building Code clauses:

- B2 Durability: Performance clauses B2.3.1(b) (i) & (ii)

Statement on how the building product is expected to contribute to compliance:

B2.3.1 (b) (i) & (ii). Powder Coated Galvanised Steel Louvre Vents have a durability of at least 15 years where the vents are installed and maintained correctly. Refer to the design and installation requirements for further information.

• options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)

• standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured

• physical properties of the building product

• how the building product is intended to be used

Limitations on the use of the building product:

Refer to Tables 20, 21 & 22 in E2/AS1 for materials that powder coated galvanised steel is suitable to be in contact with and have water run off.

Not suitable for Zone D - sea-spray zone. Refer to Section 4 of NZS 3604 : 2011 for definition of sea-spray zones.

Design requirements that would support the use of the building product:

The Louvre Vents length and width will need to be larger than the dimensions of the ventilation opening.

Installation requirements:

Use galvanised fittings to attach the flashings and paint heads with chemical metal etch primer

Apply two costs of top coat to the fitting heads

Maintenance requirements

Manual washing is required to prevent the accumulation of dirt, debris or other material not removed by rain. Walls should be washed:

- every 6 months in severe environments; and
- every 12 months in moderate environments.

Areas that do not receive adequate or any rain washing such as soffits, wall cladding under eaves, the underside of gutters, fascias, sheltered areas of garage doors, and unwashed roof areas: should be washed:

- every 3 months for severe environments; and
- every 6 months for moderate environments.

Is the building product / building product line subject to a warning or ban under section 26?:

☐Yes ☒No

If yes, description of the warning or ban under section 26:

Date: 15/11/2023